Data Sheet





AMILO Pro V2085 / V2065 Edition Your gateway to mobile working Pages 3

Issue July 2006

July / Aug. Edition

The AMILO Pro V2085/V2065 Editions are professional companions for the price-conscious, casual user. These notebooks are the ultimate balance of valuable performance and best-in-class mobility at very attractive prices.

These AMILO Pro Editions offer a crisp 15.4-inch WXGA display and ergonomic working.

The combination of AMILO Pro V2065 Edition with a large-diagonal 15.4-inch and the latest ATI Mobility™ Radeon® X300 graphics deliver the convenience of more workspace and outstanding graphics.

Ideal for users working both on the road and in the office, it features a built-in optical disk drive, modem and LAN. The Wireless LAN module offers you unlimited freedom of connectivity wherever you are.

Mobility

Valuable mobility at reasonable price

- Excellent price / performance ratio fits suiting all budgets
- Ready configured and constantly enhanced with latest technology

Convenient technology for mobile working

- Power-saving Intel® Pentium® M Processor
- Ideal connectivity through built-in Wireless LAN, LAN and modem
- Ease of use through built-in DVD writer

Ergonomics and flexibility in- and outside the office

- Enjoy the viewing quality of brilliant 15.4-inch WXGA-TFT display
- Full-size keyboard for ergonomic working
- 4 x USB (2.0) ports for easy connectivity to all peripherals and external storage devices

Robustness on the move

- Mechanical and function stability through extensive quality tests
- German quality standards
- RoHS compliant for environmental friendly working
- Award-winning best-in-class manufacturing



System	AMILO Pro V2085	AMILO Pro V2085	AMILO Pro V2065
	Edition (July/Aug)	Edition (July/Aug)	Edition (July/Aug)
Processor Intel Pentium M Processor Second level cache Front side bus (FSB)	735A (1.7 GHz)	735A (1.7 GHz)	735A (1.7 GHz)
	2048 KB	2048 KB	2048 KB
	400 MHz	400 MHz	400 MHz
Chipset Northbridge Southbridge	Intel 915GM	Intel 915GM	Intel 915PM
	ICH 6-M	ICH 6-M	ICH 6-M
Memory DDR2-533 SDRAM, 533 MHz DIMM slots	512 MB	2 x 512 MB	2 x 512MB
	2	2	2
BIOS BIOS Flash EPROM	Phoenix First BIOS	Phoenix First BIOS	Phoenix First BIOS
Interfaces Type I/II PC Card slot 3in1 Card Reader (SD, MMC and memory stick) USB 2.0 S-Video out (TV-out) VGA Modem RJ-11 LAN RJ-45 Audio-in (line-in / microphone) Audio-out (line-out / headphone) DC-in SPDIF IEEE1394 Kensington Lock	1	1	1
	1	1	1
	4	4	4
	1	1	1
	1	1	1
	1	1	1
	1	1	1
	1	1	1
	1	1	1
	1	1	1
	1	1	1
Modem on board 56K V.92 modem MDC1.5		x	x
LAN on board built-in 10/100/1000 Mbps RealTek 8110SBL LQFP 128P	X	x	х
Wireless Technologies (WLAN) Import and usage according to country-specific regulations. Dual band antenna Intel PRO/Wireless 2200BG	x	x	х
Audio Stereo speakers Sound chip	X	X	X
	ADI IC CODEC	ADI IC CODEC	ADI IC CODEC
	AD1986A	AD1986A	AD1986A
Keyboard and pointing device Keyboard Touchpad Status LED	85 keys, 19mm pitch, 2.5mm key stroke with two mouse buttons	85 keys, 19mm pitch, 2.5mm key stroke with two mouse buttons	85 keys, 19mm pitch, 2.5mm key stroke with two mouse buttons x
Graphics Intel GMA 900 with 256-bit graphics core with dynamic video memory technology up to 128MB, 32-bit color depth ATI Mobility™ Radeon® X300 graphics, 128MB Graphic, 64MB dedicated graphics memory and 64 HyperMemory™ DualView (Windows XP)	x -	x -	- x
Display 15.4-inch TFT WXGA / 1280 x 800 pixel Max. resolution for external displays	x	x	x
	1600 x 1200 / true color /	1600 x 1200 / true color /	1600 x 1200 / true color /
	85 Hz	85 Hz	85 Hz
Hard disk drives (internal) * 40 GB S-ATA 150 (5400 rpm) 80 GB S-ATA 150 (5400 rpm) * 1 Gbyte equals one billion bytes, when referring to hard disk drive capacity; accessible capacity may vary, also depending on used software and tool.	x	-	-
	-	x	X
Fixed drives DVD+/- RW Dual layer (+R) Multiformat DVD writer with double layer support * for made4you customizing projects only More information in specific Data Sheet: http://www.fujitsu-siemens.com/optical_drives/	x	x	х
Manageability DeskUpdate Driver Management Supported Standard PXE	x x x	x x x	x x x

System	AMILO Pro V2085 Edition (July/Aug)	AMILO Pro V2085 Edition (July/Aug)	AMILO Pro V2065 Edition (July/Aug)
Security	a va (a a ja va)	(3.7)	(
Physical security	_		_
Kensington Lock support	x	х	x
System Security	_		_
Norton Internet Security Symantec	x	х	x
User Security	_		_
User and supervisor BIOS password	x	х	x
Power supply			
1 st Li-Ion battery 6 cell 4400 mAH (48 Wh)	x	X	x
Battery runtime:			
First battery * (Mobile Mark 2002) [up to]	5 h	5 h	3 h
AC adapter 19V/65W Adapter			
Rated voltage (AC input) 100 - 240 V	Х	X	Х
Rated frequency 50 - 60 Hz	^	*	^
DC output 19 V, 3.42 A			
Operating temperatures			
Relative humidity (non-condensing)	20% - 85%	20% - 85%	20% - 85%
Ambient temperature	5° - 35° C	5° - 35° C	5° - 35° C
Dimensions / Weight	_		
,	24~37.5 x 359 x 273 mm	24~37.5 x 359 x 273 mm	24~37.5 x 359 x 273 mm
Weight*	2.9 kg	2.9 kg	2.9 kg
* Weight may vary depending on actual configuration			
Certificates	-		-
CE Marking	X	X	X
R&TTE	X	X	x
RoHS	X	X	X
WHQL	X	Х	X
Operating System			
Fujitsu Siemens Computers recommends Microsoft® Windows® XP Professional			
Microsoft Windows XP Professional		V	v
	X	Х	X
Software (compatibility / preinstalled) Adobe Acrobat Reader			
Driver and Utility DVD	X X	X X	X
Easy Guide on-line user documentation	X X	X X	X
Nero	_ X X	х Х	_ X X
Norton Internet Security (incl. Firewall) on Driver and Utility	^	*	^
CD	X	Х	Х
Accessories (order number)			
AC-adapter	S26391-F321-L100	S26391-F321-L100	S26391-F321-L100
Case	Value case	Value case	Value case
	S26391-F119-L50	S26391-F119-L50	S26391-F119-L50
Port Replicator	S26391-F6007-L100	S26391-F6007-L100	S26391-F6007-L100
Modem adapter set 1: D, UK	S26361-F3145-L10	S26361-F3145-L10	S26361-F3145-L10
Modem adapter set 2: SW, NO, FI, DK	S26361-F3145-L20	S26361-F3145-L20	S26361-F3145-L20
Modem adapter set 3: CH, A, B, NL, F, I, E, POR	S26361-F3145-L30	S26361-F3145-L30	S26361-F3145-L30
http://www.fujitsu-siemens.com/accessories/			

This datasheet describes the standard configuration for July / August 2006. Special configuration may vary depending on countries.